


CRAZY PAVING



ANATOLIA



ONTARIO

WHAT IS CRAZY PAVING?

It's stone-like porcelain tiles of varying shapes and sizes that have been assembled on the floor or wall in a "crazy" look

Thickness 9mm
Rectified edges
Matt

1 x box = 1.08sqm/11.63sqft. 9 shapes per box

Where can Crazy Paving be used?

- Areas like bathroom, entryways, car porch, feature wall, fireplace, External Cladding/facade, Walkways and pool area.
- In short Crazy Paving can be used on walls and floor also indoor and outdoor.

How to lay Crazy Paving?

- We recommend dry lay at least 2 square metres on the floor.
- This will help you have a good idea of the shapes and visual design you will be working with.
- Then you need to mix the shapes and colours of the tiles to make them as **crazy** as possible.
- There are only two major rules you should follow.

Rule number one:

Maintain a consistent gap of 10 to 30mm between tiles. If wider gaps are necessary, aim to keep them within 40mm.

Rule number two:

Aim to lay the tiles in a free-form manner. The goal is to maintain an organic and unstructured look and feel.

Can Crazy Paving be cut?

- Yes.

What to use to attach Crazy Paving to floor & wall?

- Tiles adhesive or Construction adhesive.

What to use in the joints/gaps between Crazy Paving?

- The gaps between the tiles can be filled with sanded grout, just add water and latex additive.

Recommended mixing ratio :

- 1kg of sanded grout : 100ml latex additive + 50ml water.
- Make sure the grout mixture is thick (not watery) to prevent shrinkage or cracking.

Do you need to seal crazy paving?

- No.

RESELLER